

EFFICIENT WARMTH WITH ELECTRIC.

Introducing the newly launched Powrmatic EUX electric unit heater, the perfect solution for commercial and industrial buildings. This wall-mounted unit provides exceptional heating performance while offering energy-saving benefits. Constructed with high-quality stainless steel, the EUX electric unit heater ensures durability and longevity.

Available in a range of sizes from 5kW to 40kW, this versatile heater meets various heating requirements. With low noise levels, it creates a comfortable environment without any disturbances.

The EUX electric unit heater is specifically designed for applications where there is no access to other heating sources such as gas, oil, or hot water. It operates at 100% efficiency and can be powered by renewable electricity, making it an environmentally-friendly choice.




Technical Specification


Model			EUX5	EUX10	EUX20	EUX30	EUX40		
Electric Power		kW	5	10	20	30	40		
		kcal/h	4,302	8,604	17,208	25,812	34,416		
Airflow Rate		m³/h	750	1200	2100	4200	5050		
Electrical Supply		V/ph/Hz	400V/3Pha/50Hz						
Degree of Protection		IP	54						
Motor Data	Power	W	70	90	150	190	250		
	Voltage	V	230						
	Current	А	0.3	0.4	0.65	0.83	1.1		
Noise		dB(A)	44	48	58	60	62		
Weight		kg	13.5	15	25	28	33		


- Each EUX unit comes complete with own controller For multiple unit control the Powrmatic MC200 is available Protection Class: IP54

Dimensions

	Model		EUX5	EUX10	EUX20	EUX30	EUX40
А	Width	mm	435	435	565	565	565
В	Height	mm	335	370	430	430	475
С	Total Depth	mm	375	380	395	395	400
D	Enclosure Depth	mm	210	210	225	225	225
E (crs)	Bracket Support crs	mm	395	395	525	525	525
F (crs)	Bracket Support crs	mm	155	155	155	155	155







POWRMATIC

Powrmatic Limited Hort Bridge, Ilminster Somerset TA19 9PS tel: **+44 (0) 1460 53535**

fax: +44 (0) 1460 52341 e-mail: info@powrmatic.co.uk



Powrmatic Ireland 45 Broomhill Close Tallaght Dublin 24

tel: **+353 (0) 1452 1533** fax: +353 (0) 1452 1764 e-mail: info@powrmatic.ie